

# INDOOR TAPS

## COMPATIBLE WITH DOCSIS 3.1

REF.	ART. NR.	DESCRIPTION	EAN 13
457103	AZ48TD	TAP 5...1218MHz "F" 4D 8dB	8424450193044
457203	AZ411D	TAP 5...1218MHz "F" 4D 11dB	8424450193051
457303	AZ414D	TAP 5...1218MHz "F" 4D 14dB	8424450193068
457403	AZ417D	TAP 5...1218MHz "F" 4D 17dB	8424450193075
457503	AZ420D	TAP 5...1218MHz "F" 4D 20dB	8424450193082
457603	AZ423D	TAP 5...1218MHz "F" 4D 23dB	8424450192993
457703	AZ426D	TAP 5...1218MHz "F" 4D 26dB	8424450193006






▲ 457103



New taps range with four derivation outputs. It allows develop distribution networks both vertically or horizontally, obtaining the greatest levels balance over all the installation.

- Distribution elements compatible with the DOCSIS 3.1 standard
- Frequency range of 5...1218MHz
- High shielding against interferences thanks to its chassis injected with Zamak
- It includes ground connection
- Screw-in mounting, this makes its installation easier



REF.	ART. NR.	 mm	 g	 U./Pack.
457103	AZ48TD	85 x 56 x 46	150	1/bag - 10/box
457203	AZ411D	90 x 56 x 40	150	1/bag - 10/box
457303	AZ414D	90 x 56 x 40	150	1/bag - 10/box
457403	AZ417D	90 x 56 x 40	150	1/bag - 10/box
457503	AZ420D	90 x 56 x 40	150	1/bag - 10/box
457603	AZ423D	90 x 56 x 40	150	1/bag - 10/box
457703	AZ426D	90 x 56 x 40	150	1/bag - 10/box



Reference	457103	457203	457303	457403	457503	457603	457703	
Connector type	F - Female							
Frequency range	5...1218 MHz							
Derivations	4							
Insertion loss(Input/Output)		4 ± 1	2 ± 1	1 ± 1	1 ± 1	1 ± 1	1 ± 1	
Derivation loss (Input/Derivation)	8 ± 1,5	11,5 ± 1,5	14 ± 1,5	17 ± 1,5	20 ± 1,5	23 ± 1,5	26 ± 1,5	
Return loss	≥12							
Insulation	≥20							
Shielding	5-30MHz	≥85						
	30-300MHz	≥85						
	300-470MHz	≥80						
	470-1000MHz	≥75						
	950-1218MHz	≥55						