

	593303	593301	593302	593304
Frequency				
Range		50- 880 Mhz and 950- 2200 Mhz		
Resolution		125 Khz		
Tuning		Frequency or channel		
Spectrum analyser				
Span		5, 10, 20, 50, 100, 200, 500 MHz and Full		
Scale		5 and 10 dB/div		
Reference level (automatic and manual)		✓		
DVB-S digital measurements [Modulation: QPSK]				
Image	✓	✓	✓	✓
Power	From 45 to 110 dBµV	✓	✓	✓
CBER	9.9E-2 – 1.0E-6	✓	✓	✓
VBER	1.0E-4 – 1.0E-8	✓	✓	✓
MER	Up to 20 dB	✓	✓	✓
C/N	Automatic	✓	✓	✓
Constellation		✓	✓	✓
SCR dCSS	EN 50494 EN 50607	✓ Upgrade 593234*		
DVB-S2 digital measurements [Modulations: QPSK, 8PSK]				
Image	✓	✓	✓	✓
Power	From 45 to 110 dBµV	✓	✓	✓
Link Margin	Up to 10 dB	✓	✓	✓
MER	Up to 20 dB	✓	✓	✓
LDPCBER	9.9E-2 – 1.0E-6	✓	✓	✓
BCHBER	9.9E-2 – 1.0E-8	✓	✓	✓
Constellation		✓	✓	✓
SCR dCSS	EN 50494 EN 50607	✓ Upgrade 593234*		
DVB-T digital measurements [Modulations: COFDM (QPSK, 16QAM, 64QAM)]				
Image	Upgrade 593231	✓	✓	✓
Power	From 45 to 110 dBµV	✓	✓	✓
	From 45 to 120 dBµV	Upgrade 593231 + Upgrade 593235*	✓ Upgrade 593235*	✓ Upgrade 593235* ✓ Upgrade 593235*
CBER	9.9E-2 – 1.0E-6		✓	✓
VBER	1.0E-3 – 1.0E-8		✓	✓
MER	Up to 35 dB		✓	✓
C/N	Automatic	Upgrade 593231	✓	✓
Echoes			✓	✓
Constetion			✓	✓
DVB-T2 digital measurements [Modulations: COFDM (QPSK, 16QAM, 64QAM and 256 QAM)]				
Image	Upgrade 593231 + Upgrade 593232	Upgrade 593232	✓	✓
Power	From 45 to 110 dBµV	Upgrade 593231 + Upgrade 593232	✓	✓
	From 45 to 120 dBµV	Upgrade 593231 + Upgrade 593232 + Upgrade 593235*	Upgrade 593232 + Upgrade 593235*	Upgrade 593235* Upgrade 593235*
LDPCBER	9.9E-2 – 1.0E-6			✓
BCHBER	1.0E-3 – 1.0E-8			✓
Link Margin	Up to 30 dB			✓
MER	Up to 35 dB	Upgrade 593231 + Upgrade 593232	Upgrade 593232	✓
C/N	Automatic			✓
Echoes				✓
Constelation				✓
DVB-C digital measurements [Modulations: 16QAM, 32QAM, 64QAM, 128QAM and 256 QAM]				
Image	✓	Upgrade 593233	Upgrade 593233	✓
Power	From 45 to 110 dBµV	✓	Upgrade 593233	✓
	From 45 to 120 dBµV	Upgrade 593235*	Upgrade 593233 + Upgrade 593235*	Upgrade 593235* Upgrade 593235*
CBER	1.E-2 – 1.0E-8	✓		✓
MER	Up to 38	✓	Upgrade 593233	✓
C/N	Automatic	✓		✓
Analogue measurements				
Level	25 and 125 dBµV	✓	✓	✓
V/A		✓	✓	✓
C/N		✓	✓	✓
Mechanical characteristics				
Weight		510g		
Dimensions		175 x 100 x 52 mm / 6.9 x 3.9 x 2 in (H x W x D)		
AC adaptor		Input: 100-240V~ 50-60Hz Output: 12VDC, 2A		
Battery		Li-ion Battery(7.2VDC, 2300mAh)		
Battery range		>4hours without LNB powering		
Resilience		It withstands drops from 1 m (3.2 ft) onto concrete on all sides		
Storage capacity		400 MB (internal) for measurements		
Interfaces		USB 2.0 for Data log download and software upgrades		
Measurements and functions				
Terrestrial plans		CCIR, CCIR + LTE, OIRT, KBW, FCC, DAB, SIM		
Satellite plans	68E INTEL C, 68E INTEL, 42E TURK, 39E HELLAS, 33E EUTEL, 28E ASTRA, 26E BADR, 25E EUTEL, 23E ASTRA, 21E EUTEL, 19E ASTRA, 16E EUTEL, 13E HOTB, 10E EUTEL, 9E EUTEL, 7E EUTEL, 4E ASTRA, 1W THORS, 1W THOR6, 5W EUTELC, 5W EUTEL, 7W NILE, 30W HISPA, 48W AMZC, 48W AMAZ, SIM			
Units		dBµV, dBmV, dBm		
LNB powering		13, 18 Vdc		
LNB tone		22 KHz		

*Free upgrade when registering the equipment